

Specification of track link ass'y for bulldozers-Lubricated type

No.	P/N	T	A	B	C	D	d	E	F	G	H	J	K	L	MODELS
1	T154GA	154	112.4	82.4	57	46.3	30	14.5	49.4	170	125.4	44	87	47	D30 D31*40
2	T155GA	155.6	104.7	88.9	54.8	47	28.6	14.5	59.5	161	121.4	48.7	88	39	D3B D3C
3	T171GA	171.5	108	108	60.3	54	33.5	16.5	74.5	182	145.5	55.6	95.2	43.2	D4D D4E
4	T175GA	175	158.4	122.4	57	55	38	18.5	84.6	218	173.2	54	101.5	58.8	D41 D50 D53A D58E
5	T203GA	203	178.4	138.4	72	66.8	44.6	19.5	101.6	244	201.6	58	116.4	64.4	D60*37 D65*37 TY160*37 T160
6	T203GB	203	171.4	133.4	76.2	69.7	44.5	19.5	102.4	232	193	58	121.5	69	D6C*44 D6D*36
7	T203GC	203	185.3	137.3	68	72.7	44.5	20.5	101.3	232	192.3	64	125	72	D6H*39
8	T216GA	216	184	146	76.2	71	47.7	19.5	108	252	208	64.3	125.5	70	D7G*38
9	T216GB	216	184	146	76.2	74.3	47	20.5	106	252	209.2	63	129	70	D80*38 D85*38 TY220*38 TY230*38
10	T228GA	228	219	169	76.2	79	48.5	24.5	121.6	292	244	71.4	138	78	D155*41 D150*41 TY320*41 SD8*43
11	T260GA	260	235	184.2	76.2	92	57	27.5	133	321	266.2	87.3	160	85	D355*39 D375 PD410*40 D9H D9G

Specification of track link ass'y for excavators-dry type

No.	P/N	T	A	B	C	D	d	E	F	G	H	J	K	L	MODELS
1	W101GA	101	55	55	22	32	19	10.5	33 35 37 42	94	76	40	63	37	PC20 PC30 SK20 EX35 YC35-6/7*41
2	W135GA	135	85	55	46	35	22.5	12.5	31.6	114	78.6	41	65	35	PC40-5
3	W135GB	135	93.8	63.8	46	35	22.5	12.5	40.4	124	87.4	41	65	35	PC40-7/8*40 PC50
4	W135GC	135	99	72	43.2	41	24	12.5	44	141	108	42.5	75	40	PC60-5*42 D20*42 SH60 E307
5	W135GD	135	104	80	46	35	22	12.5	52.5	140	106.5	40	67	31	R60 EX40-5 ZX55U
6	W135GE	135	99	72	43.4	39	22	13.5	46	141	106.6	42.4	75	34.5	DH55*42
7	W140GA	140	86	86	52	40	28	14.5	55	139	115	44	75	40	YC85*42
8	W140GB	140	86	86	52	37	25	12.3	60	139	111.4	44	72	32	FL4
9	W154GA	154	90	90	55	46.3	30	14.5	56	158	127	47.5	80	42	EX60*37
10	W154GB	154	89	73	57	41.2	24	14.5	45	130	104.2	44	74	40.5	PC60-6/7*38 PC75*39 ZX70 EX70*38 SK60-1/2/3*38 SH70 SH75 HD307 柳工907
11	W154GC	154	112.4	82.4	57	46.3	30	14.5	49.4	170	125.4	44	87	47	PC100-3*42 HD350*43
12	W171GA	171	108	108	60.3	47	30	16.5	58.6	170	129	55.57	90.2	49.5	SK100*41 SK120*43
13	W171GB	171	108	108	60.3	50.3	33.5	16.5	70	181	144.8	55.57	95	51	EX100*41 E312*46 E120B*43 SH120*44 EC140*46 EX120 EX150 R110 MS120-8 DH150 HD450 HD512 ZX120
14	W171GC	171.5	108	108	60.3	54	33.5	16.5	74.5	182	146.5	55.6	95.2	43.2	R130
15	W171GD	171	144.5	125.4	58.7	54	36.65	16.5	83.5	212	167.5	56.3	101.6	58.8	R200*50 SK07 SE210-1*50 SE210LC*54 R210LC-2 SE130LC-2 S280
16	W175GA	175	102.4	86.4	57	46.3	30	16.5	50.4	170	122.4	54	86	47	PC100-5/6*40 PC120-6*42 PC90-1*38 SK04 PC130 PC150-3*44 SY120 SY150
17	W175GB	175	158.4	122.4	57	55	38	18.5	84.6	218	173.2	54	101.5	58.8	HD700 HD770 HD1100
18	W175GC	175.4	144.5	125.4	58.7	58.75	36.5	18.5	77.5	214	169.5	57.2	103.2	59.7	EX200-1*48 SH280*49 D5B MS180
19	W190GA	190	155.6	119.6	69	58.8	36.6	20.5	82.2	220	174.2	58	106	60	E200B*45 SH200*46 SK200*46 E320*45 HD820*46 SK220*48 E317B E315B E240
20	W190GB	190	160.4	124.4	62	59	38	18.5	81.6	220	174	58	105	58	PC200-3*45 PC220-1/2/3*47 EX200-2/5*45 ZX210*46 ZX200 ZX180
21	W190GC	190	160.4	124.4	62	59	38	20.5	81.6	220	174	58	105	58	PC200-5/6/7*45 DH220-5*49 EX220*47 SE210-2/3 R220 SH220 EC210 SY200C SE280 ZX225 EX240 DS250 R250LC
22	W203GA	203	178.4	138.4	72	66.8	44.6	20.5	101.6	244	201.6	58	116.4	64.4	EX300-1*47 PC300-2*45 DH280*47 DH320*51 R280*51 EC290 R290 R320 SE280 SH300 EX270-1/5 SK300 HD1250
23	W203GB	203	178.4	138.4	72	66.8	44.6	22.5	101.6	244	201.6	58	116.4	64.4	PC300-5*47 PC250LC-6*50 PC280LC-3*51
24	W216GA	216	178.4	140.4	76.2	66.5	44.6	22.5	101.6	242	197.6	63	116	64	PC300-6/7*45 PC350-6 PC360 EX300-5*45 ZX330 ZX350
25	W216GB	216	184	146	76.2	71	47	22.5	106	252	209.2	63	129	70	EX400-1*49 PC400-1/3*49 DH450*53 R360 SE350 EC360 R350 EX400LC R450LC
26	W216GC	216	184	146	76.2	74.3	47	24.5	106	252	209.2	63	129	70	PC400-3/5*49 SH330*51 SH350 SH300 PC410-5 E345
27	W216GD	216	190	140	76.2	68	46	22.5	103	248	211	69	124	68	E330*45 SK330 SK350
28	W228GA	228	184	144	76.2	71.5	47	24.5	109	254	210	71.4	129	70	PC400-6*46 ZX500
29	W228GB	228	200	149.2	76.2	74	48.8	24.5	101.6	272	224	71.4	138	78	SH450
30	W260GA	260	235	184.2	76.2	85.3	57	27.5	133	321	266.2	87.3	152	79	PC650 EX700

NOTE:

1.The specification above is only for your reference,the final data is according to our products.

产品型号表示方式: X XXX X X
 同一规格产品序号
 产品规格形式: G-干式
 润滑形式: L-油浴式
 润滑形式: T-不上油系列
 润滑形式: L-不上油系列

